

A specialist solvent cement for jointing rigid PVC pipes and accessories in pressure systems.

Specially formulated to bond thermoplastic piping systems that conform to BS EN 1452, BS EN 1455, BS EN1566 and BS EN1329.

CONTAINS:

2-Butanone

Product Information

- Suitable for use on uPVC, muPVC and cPVC and ABS systems
- THF free
- Thixotropic
- Pack comes with brush applicator
- CE marked
- KOMO certified according to EN 14680
- AENOR certified according to EN 14814
- 2-year shelf-life

TECHNICAL DATASHEET

sizes available

125 ml and 250ml



specification

Appearance:	Thixotropic
Odour:	Characteristic
Specific Gravity @20°C:	0.87 +/- 0.01
Flash Point:	-10°C
Boiling Point:	67°C
Solubility:	Insoluble in water

Directions for Use

Saw pipes at right angles

Roughen surfaces with sandpaper

Wipe with solvent cleaner

Using a clean brush, apply an even coat of solvent cement to both surfaces

Immediately push spigot into socket and apply a quarter turn

Hold joint for a few seconds and few seconds and wipe off excess cement

Allow at least 10 minutes for joint to cure

Storage: Store in a dry and well-ventilated area, far from sources of heat and direct sunlight.