

## EasyJoint Lube

A fully biodegradable vegetable oil soap-based pipe jointing lubricant, compatible with all types of pipe material and suitable for general application.

### CONTAINS:

Saponified Mixed Acid Oil

### Product Information

- Suitable for lubricating all types of pipe material including clay, concrete and plastic land drains and ductile iron.
- Compatible with all seal materials such as EPDM, NBR, SBR, NR, CR with no 'seal swell'
- High lubricity
- Water soluble and non-toxic, fully biodegradable
- Excess material washes easily and safely away with water

### TECHNICAL DATASHEET



### sizes available

1kg, 2.5kg, 5kg and 5kg

### specification

Appearance:	Brown Gel
Odour:	Characteristic odour
pH:	10.0 Typical
Specific Gravity @20°C:	1.02 +/- 0.02
Soap Content:	28% min
Free Caustic Alkali:	0.5% max
Total Free Alkali:	1.0% max

### Directions for Use

Ensure ring seal, socket and pipe end are clean and free from dirt

Ensure the seal is correctly located in the seal housing of the socket

Mark the correct insertion depth on pipe end

Apply a thin film of lubricant evenly to pipe end (especially the chamfer), gasket and inside the socket

Push pipe end into socket until pipe insertion mark indicates the pipe has been jointed to the correct socket depth

**Storage:** Store in the original containers out of direct sunlight with the lids securely closed.