

EasyJoint SO

EasyJoint SO is a pure silicone oil lubricant suitable for jointing plastic pipes.

This unique silicone oil lubricant is suited to lubricating 'O' rings and pipe joints during the assembly of push-fit soil and water waste water.

CONTAINS:
Silicone Oil

Product Information

- Used in uPVC push-fit soil and waste water systems to lubricate 'O' rings and pipe joints during assembly
- Low viscosity (5cst) gives high spreading capability
- Compatible with all common 'O' ring materials (EPDM, NBR, SBR, NR, CR) with no 'seal swell'
- Stable in daylight and UV light between -50°C and +280°C
- Excellent water and weather resistance
- Non-toxic and inert

TECHNICAL DATASHEET

sizes available

5ltr



specification

Appearance:	Colourless Viscous Liquid, slippery to the touch
Odour:	No odour
Flashpoint:	~280°C
Relative Density:	~0.96
Solubility:	Soluble in water

Directions for Use

Ensure ring seal, socket and pipe end are clean and free from dirt.

Check that the seal is correctly located in the seal housing of the socket.

Apply a thin film of lubricant evenly to pipe end (especially the chamfer), gasket and inside the socket.

Push pipe end into socket to required depth.

Storage: Keep in original packaging. Store in a cool dry well-ventilated area out of direct sunlight.