

ConnectaPipe

EasyJoint Wax

A complex blend of natural technologies that gives water resistance and provides excellent lubricity properties under high loads.

CONTAINS:

Wax and Silicone Oil

Product Information

- For use with Clay and Concrete and HDPE plastic pipe material for soil and waste water installations
- Some cold water wash off resistance with enhanced lubricity properties for heavy duty pipes
- Pipes can be laid in wet conditions
- Compatible with all known seal materials such as EPDM, SBR, NBR, NR, CR with no 'seal swell'

TECHNICAL DATASHEET



sizes available

1Kg and 2.5Kg

specification

Appearance:	White coloured viscous paste
-------------	------------------------------

Odour:	No odour
--------	----------

pH:	7.0 Typical
-----	-------------

Specific Gravity @20°C:	1.02 +/- 0.02
-------------------------	---------------

Directions for Use

Ensure ring seal, socket and pipe end are clean and free from dirt

Ensure the seal is correctly located in the seal housing of the socket

Mark the correct insertion depth on pipe end

Apply a thin film of lubricant evenly to pipe end (especially the chamfer), gasket and inside the socket

Push pipe end into socket until pipe insertion mark indicates the pipe has been jointed to the correct socket depth

Storage: Store in original packaging in a cool, dry and well-ventilated area out of direct sunlight.



DELTA (UK) LTD · Unit 2 Hickmans Road · Birkenhead · Wirral · CH41 1JH · United Kingdom
Tel. +44 (0) 151 630 0405 · Fax. +44 (0) 151 630 0406 · Email info@delf-uk.com

